



See page 36 for details

# UP19-VR

18 mm Ø, 2 mW - 35 W, Volume Absorber



## KEY FEATURES

### 1. MODULAR CONCEPT

Increase the power capability of your detector: 2 different cooling modules

### 2. HIGH PEAK POWER VOLUME ABSORBER

- Perfect for high density beams
- Average power density of 700 W/cm<sup>2</sup> prevents degradation caused by repetitive pulses

### 3. COMPACT DESIGN

Only 21 mm thick (15S model)

### 4. ENERGY MODE

Measure single shot energy up to 40 J

### 5. SMART INTERFACE

Containing all the calibration data

## AVAILABLE MODELS



UP19K-15S-VR  
(15W-Standalone)



UP19K-30H-VR  
(30W-Heatsink)

## ACCESSORIES



Stand with Steel Post  
(Model Number: 200160)



Extension Cables  
(4, 15, 20 or 25 m)



Pelican Carrying Case

## SEE ALSO

HOW IT WORKS	14
CALIBRATION	6
TECHNICAL DRAWINGS	86
ABSORPTION CURVES	90
COMPATIBLE MONITORS	
MAESTRO	20
TUNER	24
UNO	26
S-LINK	28
P-LINK	30
M-LINK	32
LIST OF ALL ACCESSORIES	190

# UP19-VR

## SPECIFICATIONS



\*Also traceable to NRC-CNRC

	UP19K-15S-VR	UP19K-30H-VR
<b>MAX AVERAGE POWER (CONTINUOUS / 1 MINUTE)</b>	15 W / 20 W	30 W / 35 W
<b>EFFECTIVE APERTURE</b>	18 mm Ø	18 mm Ø
<b>COOLING METHOD</b>	Convection	Heatsink
<b>MEASUREMENT CAPABILITY</b>		
Spectral Range <sup>*a</sup>	0.3 – 2.5 µm	0.3 – 2.5 µm
Noise Equivalent Power <sup>b</sup>	2 mW	2 mW
Rise Time (nominal) <sup>c</sup>	2.5 sec	2.5 sec
Sensitivity (typ into 100 kΩ load) <sup>d</sup>	0.34 mV/W	0.34 mV/W
Calibration Uncertainty <sup>e</sup>	±2.5 %	±2.5 %
Repeatability	±0.5 %	±0.5 %
Energy Mode		
Sensitivity	0.1 mV/J	0.1 mV/J
Maximum Measurable Energy <sup>f</sup>	40 J	40 J
Noise Equivalent Energy <sup>b</sup>	0.02 J	0.02 J
Minimum Repetition Period	4.5 sec	4.5 sec
Maximum Pulse Width	90 ms	90 ms
Accuracy with energy calibration option	±5 %	±5 %
<b>DAMAGE THRESHOLDS</b>		
Maximum Average Power Density <sup>g</sup>	700 W/cm <sup>2</sup>	700 W/cm <sup>2</sup>
Pulsed Laser Damage Thresholds	Max Energy Density	Peak Power Density
1064 nm, 360 µs, 10 Hz	40 J/cm <sup>2</sup>	111 kW/cm <sup>2</sup>
1064 nm, 7 ns, 10 Hz	6 J/cm <sup>2</sup>	860 MW/cm <sup>2</sup>
532 nm, 7 ns, 10 Hz	4 J/cm <sup>2</sup>	570 MW/cm <sup>2</sup>
266 nm, 7 ns, 10 Hz	1 J/cm <sup>2</sup>	143 MW/cm <sup>2</sup>
<b>PHYSICAL CHARACTERISTICS</b>		
Effective Aperture	18 mm Ø	18 mm Ø
Absorber (Volume Absorber)	VR	VR
Dimensions	50H x 50W x 20.6D mm	50H x 50W x 56.3D mm
Weight (head only)	0.16 kg	0.21 kg
<b>ORDERING INFORMATION</b>		
Product Name	UP19K-15S-VR	UP19K-30H-VR
Product Number (Including stand)	201149	201150
INTEGRA Product Name	UP19K-15S-VR-INT	UP19K-30H-VR-INT

\* For the calibrated spectral range, see the user manual.

- a. Adjustment multipliers for wavelengths under 300 nm are not traceable.  
 b. Nominal value, actual value depends on electrical noise in the measurement system.  
 c. With Gentec-EO MAESTRO, UNO, P-LINK, TUNER and S-LINK monitors.  
 d. Maximum output voltage = sensitivity x maximum power.

- e. Including linearity with power.  
 f. For 360 µs pulses. Higher pulse energy possible when customized for long pulses (ms), less for short pulses (ns).  
 g. At 1064 nm, 10 W CW.

Specifications are subject to change without notice